

<b>RIF. BB</b>	<b>RICAMBIO OPTIMA</b>	<b>ANGOLO DI SPRUZZO</b>	<b>ORIFIZIO 0.000" mm</b>	
ON207	218	20°	0.007	0.18
ON307	318	30°	0.007	0.18
ON407	418	40°	0.007	0.18
ON507	518	50°	0.007	0.18
ON507	618	60°	0.007	0.18
ON209	223	20°	0.009	0.23
ON309	323	30°	0.009	0.23
ON409	423	40°	0.009	0.23
ON509	523	50°	0.009	0.23
ON609	623	60°	0.009	0.23
ON211	228	20°	0.011	0.28
ON311	328	30°	0.011	0.28
ON411	428	40°	0.011	0.28
ON511	528	50°	0.011	0.28
ON611	628	60°	0.011	0.28
ON213	233	20°	0.013	0.33
ON313	333	30°	0.013	0.33
ON413	433	40°	0.013	0.33
ON513	533	50°	0.013	0.33
ON613	633	60°	0.013	0.33
ON215	238	20°	0.015	0.38
ON315	338	30°	0.015	0.38
ON415	438	40°	0.015	0.38
ON515	538	50°	0.015	0.38
ON615	638	60°	0.015	0.38
ON217	243	20°	0.017	0.43
ON317	343	30°	0.017	0.43
ON417	443	40°	0.017	0.43
ON517	543	50°	0.017	0.43
ON617	643	60°	0.017	0.43
ON001	1196-24	Guarnizione		